



- Possibilities to operate:
1. VBG valve box
 2. C- connector
 3. Palm- connector
 4. Duomatic-connector
- Betätigungsmöglichkeiten:
1. VBG Ventilkasten
 2. C- Verbinder
 3. Palm-Verbinder (Kupplungskopf standard rot)
 4. Duomatik verbindung

RINGFEDER
 Selbsttätige Bolzenkupplung Typ 5050 AM n.
 Zur Verbindung mit Zugösen 50 DIN 74053 oder ISO 1102

C50-X Fabr.-Nr. **Bj.**

(E11) 55R - 01 6289 D 200 kN
 Dc 135 kN
 S 1000 kg S 2000 kg S 2500 kg
 V 75 kN V 63 kN V 50 kN

VBG GROUP AB, Sweden

Winkelausschläge der Zugöse D50 / angles of drawbar eye D50:
 Horizontal : ±110°
 Vertikal : ±20°
 Axial : 360° bei einem Mindest-Drehmoment von 100Nm /
 360° if using minimum tightening torque of 100Nm

VBG GROUP		Modified Date 2014-03-31	Modified by HBH	Modification No. 12202	Issue b
Description Type 5050 AM/RL		3D Model No. 14999655	Engineer HBH	Checked by HBH	
Stage A1	Drawing No. 1.2	Revision P	Drawing Date 2005-12-06	Drafted by HBH	
P 14999655-info <small>This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program; this concerns both 2D & 3D.</small>					