



Possibilities to operate:

1. VBG valve box
2. C- connector
3. Palm- connector
4. Duomatic-connector

Betätigungsmöglichkeiten:

1. VBG Ventilkasten
2. C- Verbinder
3. Palm-Verbinder (Kupplungskopf standard rot)
4. Duomatik verbindung

ECE-Typgenehmigung:
ECE-type approval:

E11 55R - 01 6291

zur Verbindung mit Zugösen:

Selbsttätige, nicht genormte Bolzenkupplung der Klasse S
Zugösen 40 mm gemäß ISO 8755 oder DIN 74054
Automatic non standard drawbar coupling class S
Drawbar eyes 40 mm acc. to ISO 8755 or DIN 74054

suitable for connection with drawbar eyes:

Winkelausschläge der Zugöse:
angles of drawbar eye:

Horizontal ± 110°
Vertikal ± 20°
Axial ± 360° bei einem Mindest-Drehmoment von 100 Nm
if applying minimum torque of 100 Nm

D: 137 kN
Dc: 92 kN
V: 40kN
S: 1000kg

Fastening torques according to mounting instruction
Anzugsmomente gemäß Montageanleitung

		Modified Date	Modified by	Modification No.	Issue
		2023-05-04	HBH	14046	a
VBG GROUP		3D Model No.	Engineer		
		15990915	HBH		
Description	Sheet Size	Scale	Projection	Drafting Date	Drafted by
	RF40 G150 AM CD	A2	1:4	2023-05-04	HBH
Stage		Drawing No.			
P		15990915(Info)			
<small>This drawing is the property of VBG Group AB and is protected in accordance with prevailing law. Changes must be made in CAD-program, this concerns both 2D & 3D.</small>					